

a liquid crystal material over the orientation film, said liquid crystal material having a chiral smectic C_R phase and being continuously switched according to an electric field applied thereto,

said method comprising the steps of:

displaying a black level by the liquid crystal material in a first period;

applying a voltage to the liquid crystal material for a gradation display in a second period,

wherein the second period comes before or after the first period.

2. A method of driving a liquid crystal display device,

said liquid crystal display device including:

an orientation film over a substrate; and

a liquid crystal material over the orientation film, said liquid crystal material having a chiral smectic C_R phase and being continuously switched according to an electric field applied thereto,

said method comprising the steps of:

canceling out a spontaneous polarization of the liquid crystal material in a first period; and

applying a voltage to the liquid crystal material for a gradation display in a second period,

wherein the second period comes before or after the first period.

3 (Amended). A method of driving a liquid crystal display device:

said liquid crystal display device including:

an orientation film over a substrate; and

B2
a liquid crystal material over the orientation film, said liquid crystal material having a chiral smectic C_R phase and being continuously switched according to an electric field applied thereto,

said method comprising the steps of:

applying a voltage of 0V to the liquid crystal material in a first period; and

applying a voltage to the liquid crystal material for a gradation display in a second period,

wherein the second period comes before or after the first period.

4. A method according to claim 1,

wherein a plurality of active elements are formed over the substrate.

5. A method according to claim 4,

wherein each of the plurality of active elements applies a voltage to the liquid crystal material, and

wherein the voltage has an upper limit.

6. A method according to claim 5,

wherein the upper limit of the voltage has an absolute value of 7 V or less.

7. A method according to claim 1,
wherein a spontaneous polarization of the liquid crystal material is 40 nC/cm^2 - 150 nC/cm^2 , and
wherein a thickness of the orientation film is 15 nm - 75 nm .
8. A method according to claim 1,
wherein a spontaneous polarization of the liquid crystal material is 20 nC/cm^2 - 40 nC/cm^2 , and
wherein a thickness of the orientation film is 30 nm - 150 nm .
9. A method according to claim 1,
wherein a spontaneous polarization of the liquid crystal material is 40 nC/cm^2 or less.
10. A method according to claim 1,
wherein a first response time is defined as a response time of the liquid crystal material between a first voltage and a second voltage having an opposite polarity to the first voltage not via a voltage of 0V ,
wherein a second response time is defined as a response time of the liquid crystal material between a first voltage and a second voltage having an opposite polarity to the first voltage via the voltage of 0V ,
wherein the second response time is five times or more as short as the first response time.

11. A method according to claim 4,
wherein each of the plurality of active elements is connected in series to an auxiliary
capacitor.

12 (Amended). A method of driving a liquid crystal display device,
said liquid crystal display device including:

B2
a plurality of thin film transistors being provided over a substrate;
an auxiliary capacitor being connected in series to each of the plurality of thin
film transistors;
an orientation film over each of the plurality of thin film transistors; and
a liquid crystal material over the orientation film, said liquid crystal material
having a spontaneous polarization and being continuously switched according to an electric field
applied thereto,

said method comprising the steps of:

applying a voltage of 0V to the liquid crystal material in a first period; and
performing a gradation display in a second period,
wherein the second period comes before or after the first period,
wherein the first period and the second period repeat.

13. A method according to claim 12,

wherein a transmittance of the liquid crystal material is uniquely determined when

voltages having a same absolute value and opposite polarities are applied thereto.

14. A method according to claim 12,

wherein the liquid crystal material has a same tilt angle when voltages having a same absolute value and opposite polarities are applied thereto.

15. A method according to claim 12,

wherein the liquid crystal material has a chiral smectic C_R phase.

16. A method according to claim 1,

wherein a spontaneous polarization of the liquid crystal is 100 nC/cm^2 or less, and

wherein the thickness of the orientation film is 75 nm or less.

17. A method according to claim 2,

wherein a plurality of active elements are formed over the substrate.

18. A method according to claim 17,

wherein each of the plurality of active elements applies a voltage to the liquid crystal material, and

wherein the voltage has an upper limit.

19. A method according to claim 18,

wherein the upper limit of the voltage has an absolute value of 7 V or less.

20. A method according to claim 2,

wherein the spontaneous polarization of the liquid crystal material is 40 nC/cm^2 - 150 nC/cm^2 , and

wherein a thickness of the orientation film is 15 nm - 75 nm.

21. A method according to claim 2,

wherein the spontaneous polarization of the liquid crystal material is 20 nC/cm^2 - 40 nC/cm^2 , and

wherein a thickness of the orientation film is 30 nm - 150 nm.

22. A method according to claim 2,

wherein the spontaneous polarization of the liquid crystal material is 40 nC/cm^2 or less.

23. A method according to claim 2,

wherein a first response time is defined as a response time of the liquid crystal material between a first voltage and a second voltage having an opposite polarity to the first voltage not via a voltage of 0V,

wherein a second response time is defined as a response time of the liquid crystal material between a first voltage and a second voltage having an opposite polarity to the first voltage via the voltage of 0V,

wherein the second response time is five times or more as short as the first response time.

24. A method according to claim 17,
wherein each of the plurality of active elements is connected in series to an auxiliary capacitor.

25. A method according to claim 2,
wherein the spontaneous polarization of the liquid crystal is 100 nC/cm^2 or less, and
wherein the thickness of the orientation film is 75 nm or less.

26. A method according to claim 3,
wherein a plurality of active elements are formed over the substrate.

27. A method according to claim 26,
wherein each of the plurality of active elements applies a voltage to the liquid crystal material, and
wherein the voltage has an upper limit.

28. A method according to claim 27,
wherein the upper limit of the voltage has an absolute value of 7 V or less.

29. A method according to claim 3,
wherein a spontaneous polarization of the liquid crystal material is $40 \text{ nC/cm}^2 - 150 \text{ nC/cm}^2$, and
wherein a thickness of the orientation film is $15 \text{ nm} - 75 \text{ nm}$.
30. A method according to claim 3,
wherein a spontaneous polarization of the liquid crystal material is $20 \text{ nC/cm}^2 - 40 \text{ nC/cm}^2$, and
wherein a thickness of the orientation film is $30 \text{ nm} - 150 \text{ nm}$.
31. A method according to claim 3,
wherein a spontaneous polarization of the liquid crystal material is 40 nC/cm^2 or less.
32. A method according to claim 3,
wherein a first response time is defined as a response time of the liquid crystal material between a first voltage and a second voltage having an opposite polarity to the first voltage not via the voltage of 0V ,
wherein a second response time is defined as a response time of the liquid crystal material between a first voltage and a second voltage having an opposite polarity to the first voltage via the voltage of 0V ,
wherein the second response time is five times or more as short as the first response time.

33. A method according to claim 26,
wherein each of the plurality of active elements is connected in series to an auxiliary
capacitor.

34. A method according to claim 3,
wherein a spontaneous polarization of the liquid crystal is 100 nC/cm^2 or less, and
wherein the thickness of the orientation film is 75 nm or less.

[Please add the following new claims:]

35(New). A method according to claim 1,
wherein said liquid crystal material is driven by active matrix driving.

A4
36 (New). A method according to claim 2,
wherein said liquid crystal material is driven by active matrix driving.

37 (New). A method according to claim 3,
wherein said liquid crystal material is driven by active matrix driving.

38 (New). A method according to claim 1,
wherein said black level is displayed by applying a voltage of 0V to the liquid crystal material.

39 (New). A method according to claim 1,